

WCS, WALL-MOUNTED WC, TOILETS, SIPHONIC TOILETS, WALL-MOUNTED
TOILETS SUBWAY

PRODUCT INFORMATION

1 . POSITION



Model	5614UR
Width	14 5/8" inch
Depth	22" inch
Weight	55,56 lbs
Description	<p>DirectFlush washdown model Sanitary ceramics this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts. incl. "Supra-Fix 3.0" mounting system EN 997 Please order toilet seat separately. This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22" (560mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall- mounted toilet is Villeroy & Boch model 5614UR ADA compliant, EPA - Watersense, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, Code Compliance: UPC, IPC, NSPC, NPC Canada and others washdown model concealed trapway D-shape bowl one year limited warranty min Water pressure: 8 psi water surface: 4" x 5" (100 x 130 mm) trap diameter: 2" (50mm) trap seal: 2 3/8" (60mm) minimum rough-in: 7" (180 mm) rough-in rear outlet</p>
Water use	0,79 / 1,19 gal
Installation	wall-mounted
Outlet	concealed trapway
Material	Sanitary ceramics
Leed	4

Specification texts

; Wall-mounted toilet with rimless flushing (Directflush); DirectFlush; Sanitary ceramics; Size: 14 5/8" x 22" (370 x 560 mm); Oval; washdown model; wall-mounted; this product works with industry standard in-wall carrier/tank systems such as those manufactured by Viega, Geberit and TOTO. Please refer to their respective compatibility charts.; Water use: 0,79 / 1,19 gal; Leed: 4; incl. "Supra-Fix 3.0" mounting system; EN 997; concealed trapway; Please order toilet seat separately.; This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22" (560mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5614UR; ADA compliant, EPA - Watersense, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14, Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, Code Compliance: UPC, IPC, NSPC, NPC Canada and others; washdown model; concealed trapway; D-shape bowl; one year limited warranty; min Water pressure: 8 psi; water surface: 4" x 5" (100 x 130 mm); trap diameter: 2" (50mm); trap seal: 2 3/8" (60mm); minimum rough-in: 7" (180 mm) rough-in; rear outlet

COLOURS

White Alpin	5614UR01	4051202373092
White Alpin CeramicPlus	5614URR1	4051202373108

TECHNICAL DRAWINGS

5614UR

