

WCS, FLOOR-STANDING WC, TOILETS, 1PC-SIPHONIC, FLOOR-MOUNTED TOILETS STRADA

PRODUCT INFORMATION

1 . POSITION



Model	5650US
Width	14 3/8" inch
Depth	28 3/4" inch
Weight	114,64 lbs
Description	<p>Sanitary ceramics 12" rough-in incl. SoftClosing WC seat 9M04 S1 01 composed of: Consisting of: Siphonic WC, rough in 12" from the wall, Tank, bottom inlet, flushing mechanism with chrome trip lever, WC-seat and cover with QuickRelease and SoftClosing hinges 9M30 U1 01, incl. fastening set Please order toilet seat separately. This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 28 7/8" (735mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5650US Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14 siphonic jet model concealed trapway elongated bowl one year limited warranty min Water pressure: 8 psi minimum rough-in: 12" (305 mm) rough-in bottom outlet</p>
Installation	floor-standing
Outlet	concealed trapway
Material	Sanitary ceramics
Lead	4

Specification texts

; One-piece toilet; Sanitary ceramics; Size: 14 3/8" x 28 3/4" (365 x 730 mm); Oval; floor-standing; 12" rough-in; Leed: 4; incl. SoftClosing WC seat 9M04 S1 01; concealed trapway; Please order toilet seat separately.; This one-piece toilet is made of vitreous china. The one-piece toilet is 28 3/4" (730mm) x 14 3/8" (365mm) x 28 7/8" (735mm). The product has a concealed trapway and an elongated bowl. The product has a water use of 1.28 gpf (4.8 lpf). The one-piece toilet is Villeroy & Boch model 5650US; Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others, Certifications: IAPMO(cUPC), State of Massachusetts, ADA compliant, meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14; siphonic jet model; concealed trapway; elongated bowl; one year limited warranty; min Water pressure: 8 psi; minimum rough-in: 12" (305 mm) rough-in; bottom outlet

COLOURS

White Alpin 5650US01 4051202558994

TECHNICAL DRAWINGS

5650US

